GPS/GSM组合天线 GPS/GSM

产品名称	GPS/GSM组合天线 GPS/GSM
公司名称	嘉兴市穿云电子科技有限公司
价格	.00/个
规格参数	品牌:GPS/GSM 型号:GPS/GSM-03 增益:3
公司地址	嘉兴市东栅经济园纬一西路101号综合楼B幢
联系电话	13362302892

产品详情

品牌	GPS/GSM	型号	GPS/GSM-03
增益	3	频率范围	5（MHz）

（i）dielectric antennacenter frequency 1575.42mhz±3 mhzv.s.w.r 1.5:1band width ±5 mhzimpedance 50 ohmpeak gain ＞3dbic based on 7×7cm ground planegain coverage ＞-4dbic at -90 ° ＜0＜+90 °（over 75% volume)polarization rhcp（ii）gsm antennacenter frequency 850/1900mhz or 900/1800mhzv.s.w.r 2.0:1impedance 50 ohmtypical gain2dbi+/-1db@850mhz;2dbi+/-1db@900mhz;1dbi+/-1db@1800mhz;1dbi+/-1db@1900mhz（iii）lna/filterlna gain(without cable) 28db typicalnoise figure 1.5dbfilter out band attenuation (f0=1575.42 mhz)7db min f0+/-20mhz ;20db min f0+/-50mhz;30db min f0+/-100mhzv.s.w.r ＜2.0dc voltage 2.7v/3.0v/3.3v/5.0v/3.0v to 5.0v/otherdc current 11ma max（iv）mechanicalweight ＜240gramsize 65mm x 38.5mm x37mmcable gps-----rg174 2meter, 5meter long or othergsm-----rg174 2meter, 5meter long or otherconnector gps-----sma/smb/smc/bnc/fme/tnc/mcx /mmcx or othergsm----sma/smb/smc/bnc/fme/tnc/mcx/mmcx or othermounting screw mountinghousing black（v） environmentalworking temp. -40°C~+85°Cstorage temp. -45°C~+100°Cvibration sine sweep 1g(0-p)10~50~10hz each axishumidity humidity95%~100%rhweatherproof 100%waterproof