

GPS/GSM组合天线 GPS/GSM

产品名称	GPS/GSM组合天线 GPS/GSM
公司名称	嘉兴市穿云电子科技有限公司
价格	.00/个
规格参数	品牌:GPS/GSM 型号:GPS/GSM-03 增益:3
公司地址	嘉兴市东栅经济园纬一西路101号综合楼B幢
联系电话	13362302892

产品详情

品牌	GPS/GSM	型号	GPS/GSM-03
增益	3	频率范围	5 (MHz)

(i) dielectric antenna center frequency 1575.42mhz \pm 3 mhz v.s.w.r 1.5:1 band width \pm 5 mhz impedance 50 ohm peak gain > 3dbic based on 7 x 7cm ground plane gain coverage > -4dbic at -90 ° < 0 < +90 ° (over 75% volume) polarization rhcp (ii) gsm antenna center frequency 850/1900mhz or 900/1800mhz v.s.w.r 2.0:1 impedance 50 ohm typical gain [2dbi+/-1db@850mhz;2dbi+/-1db@900mhz;1dbi+/-1db@1800mhz;1dbi+/-1db@1900mhz](#) (iii) Ina/filter Ina gain (without cable) 28db typical noise figure 1.5db filter out band attenuation (f0=1575.42 mhz) 7db min f0+/-20mhz ;20db min f0+/-50mhz;30db min f0+/-100mhz v.s.w.r < 2.0 dc voltage 2.7v/3.0v/3.3v/5.0v/3.0v to 5.0v/other dc current 11ma max (iv) mechanical weight < 240grams size 65mm x 38.5mm x 37mm cable gps-----rg174 2meter, 5meter long or other gsm-----rg174 2meter, 5meter long or other connector gps-----sma/smb/smc/bnc/fme/tnc/mcx /mmcx or other gsm-----sma/smb/smc/bnc/fme/tnc/mcx/mmcx or other mounting screw mounting housing black (v) environmental working temp. -40 ~+85 storage temp. -45 ~+100 vibration sine sweep 1g(0-p)10~50~10hz each axis humidity humidity 95%~100%rh weatherproof 100% waterproof