HDPE 美国陶氏 CS K-3364 NT

产品名称	HDPE 美国陶氏 CS K-3364 NT
公司名称	东莞市湘远塑胶有限公司
价格	.00/千克
规格参数	美国陶氏:CS K-3364 NT 薄壁绝缘:电线电缆应用
公司地址	深圳市龙岗区龙城街道盛平村委田段心南十二巷2号101
联系电话	13532886152

产品详情

AXELERON CS K-3364 NT CPD 物性表

基本信息

- 用途

薄壁绝缘

电话绝缘体

电线电缆应用

固体绝缘

通信电线绝缘材料

机构	NF C 32-060	
物理性能额定值单位制测试方法	ASTM D 1248, III, Class A, Cat. 4, Grade E8	
密度	ASTM D 1248, III, Class A, Cat. 4, Grade E9	0.947
熔流率（熔体流动速率） (190 ° C/2.16 kg)	BS 6234 Type H03	0.75
	EN 50290-2-23	
抗环境应力开裂 (100 ° C, 100 Igepal, F0)	FED L-P-390C, Type II, Class H, Category 4, Grade 1	> 48.0
	ICEA S-84-608	
机械性能额定值单位制测试方法	IEC 60708	23.4
伸长率 (断裂)		500
老化额定值单位制测试方法		
拉伸强度保持率 - 48 hrs (100 ° C)		90
伸长保持率 - 48 hrs (100 ° C)		90
热性能额定值单位制测试方法		
耐热应力裂纹 - 10		> 96
脆化温度 1		-76.0
电气性能额定值单位制测试方法		
体积电阻率 (23 ° C)		> 1.0E+15

耗散因数 (1 MHz)	6.0E-3
熔体密度	218 到 260
挤出额定值单位制	
挤压说明	

AXELERON CS K-3364 NT CPD provides excellent surface finish and good output rates over a broad range of extrusion conditions. AXELERON CS K-3364 NT CPD is typically extruded at melt discharge temperatures ranging from 218-260 ° C (425-500 ° F) using conductor preheats ranging from 110-140 ° C (230-290 ° F). Specific extrusion conditions can be recommended only when the application, processing speed and processing equipment details are known.