喜洋洋防裂宝胶粘剂 接缝王

产品名称	喜洋洋防裂宝胶粘剂 接缝王
公司名称	江西亚太化工有限公司
价格	.00/个
规格参数	型号:防裂宝 品牌:万古牌 树脂胶的分类:环氧树脂胶
公司地址	江西省宜春市袁州区工业园
联系电话	0795-3668458

产品详情

型号	防裂宝	品牌	万古牌
树脂胶的分类	环氧树脂胶	粘合材料类型	其他

【应用范围】

室内外装修中木质、石膏板、硅酸钙板、铝合金窗、混凝土墙体相互之间的缝隙的粘接与填充，渗和水泥可起到防渗漏作用。广泛用于家庭、宾馆、酒店、歌舞厅等装修中容易开裂的部位。

【性能特点】

本产品为调和性的胶体腻子，使用方便，具有极强的粘接性和耐候性，干固适中，安全环保。

【使用方法】

用前摇匀，按a：b=1：0.25~0.3的比例调和（夏天气温高b料可稍少，冬天气温低b料稍可增加），静止1~2分钟，加入适量的c料调成胶状腻子，直接刮进需要粘接的缝隙内，刮平即可。顶部和立面的缝隙在刮平后30分钟内再刮一次。

详情请登入公司网站，了解公司更多产品信息：http://www.ythg.net/index.asp

applications: it decorated between indoor and outdoor and the decoration of wood, gypsum board, calcium silicate board, aluminum alloy windows, concrete wall and the crack among them , the adhesive and filling .seepage and cement could play in an anti-leakage role . it is widely used in family, hotel, hotels, dance halls, etc.the renovation of the site is easy to crack.

performance and characteristics:this product is colloidal reconcile putty, easy to use, has very strong adhesion and weather resistance, medium dry and solid, safety and environmental protection

directions: before use it, shake itwell, according to a: b = 1:0.25 ~ 0.3 to reconcile the ratio of (the summerishigh temperature can usea little less material b, winter temperatures is expected to increase slightly) still it 1 to 2 minutes, adding an appropriate amount of c to tune into a gelatinous putty .,directly add it into the gap, when scratch it evenly , and the elevation at the top of the gap in 30 minutes after scratch it again