

PMP日本三井(RT18)

产品名称	PMP日本三井(RT18)
公司名称	东莞市华韵塑胶原料有限公司
价格	88.00/kg
规格参数	PMP:耐热级 RT18:耐化学 日本三井:LED模条专业原料
公司地址	东莞市樟木头镇奥园塑金国际8栋214
联系电话	0769-87600377 13556776933

产品详情

PMP日本三井(RT18)

PMP 日本国三井化学 RT-18

华韵现货交易 PMP 日本国三井化学 MX002

华韵现货交易 PMP 日本国三井化学 MX004

华韵现货交易 PMP 日本国三井化学 DX820

华韵现货交易 PMP 日本国三井化学 MX020

华韵现货交易 PMP 日本国三井化学 RT18XB

华韵现货交易 PMP 日本国三井化学 DX810

华韵现货交易 PMP 日本国三井化学 DX845

华韵现货交易 PMP 日本国三井化学 T110

华韵现货交易 PMP 日本国三井化学 MX001

华韵现货交易 PMP 日本国三井化学 DX310

华韵现货交易 PMP 日本国三井化学 MLL411

华韵现货交易 PMP 日本国三井化学 RT18(粉)

华韵现货交易 PMP 日本国三井化学 MX004(粉)

Main applications: AS RELEASE FILM FOR FPC Leading Circuit Board and raw material, its main uses are very common, used for making LED mould, medical needles, laboratory equipment, fully transparent chemical plant equipment, food packaging materials, lighting lamps and lighting lamps, car components, fully transparent package raw materials, cable and cable sheath, can also be used as pipe fittings, film bags, coating, etc. . Note: This enterprise can apply to a variety of raw materials with the purchase, 25 kg / pack ordered, large quantities can be discounted, product description TPX alias poly4-hydroxypentene-1 individual 4-hydroxypentene-1 primary poly4-hydroxypentene-1 is a highly crystalline transparent plastic with a ratio of 0.83. It is the lightest of all plastics. Low surface strength, non-toxic. The transmittance is close to the middle of the plexiglass plate and the polyethylene. Ignition characteristics, can be ignited, Xuan fire after slow ignition again, there are melting dripping down. Advantage TPX transmissivity does not change with the standard of production and processing, neither with the thickness of the commodity and change, therefore, suitable for making fully transparent products. Its stiffness exceeds that of polypropylene above 100 ° C and that of PC above 150 ° C