

永创通达立柱式码垛机 膜包纸箱高速码垛机YCMD55

产品名称	永创通达立柱式码垛机 膜包纸箱高速码垛机YCMD55
公司名称	北京永创通达机械设备有限公司
价格	100.00/台
规格参数	品牌:永创通达 型号:YCMD55 产地:河北大名
公司地址	北京市大兴区西红门镇兴创国际中心A座19层
联系电话	010-89229189 15201067035

产品详情

YCMD55

立柱式码垛机

pillar type stacker crane

产品特点

FEATURES:

液晶彩屏，操作界面友好，参数设定快捷，码垛对照编组通用、适应性强。

坐标轴移动码垛平台：低（位）输送高（位）码垛的形式，打破了传统的高速码垛机不能低位输送的形式。

采用先进制造工艺：码垛机立柱和横臂滑轨的安装面、安装孔均是在高精度的龙门铣床上一次装卡加工而成的，精度高、噪音少、更稳定。

整机依据指令全自动运行，故障自动检测和报警，高安全性和可靠性。占地面积比传统码垛机小1/3,能耗为原来的1/3。

可实现纸箱码垛或收缩膜包装产品的码垛，配备多种安全防护措施。

LCD color screen, friendly operation interface, parameter setting easily, pallet marshalling is in common use, strong adaptability

Coordinate axis translational pallet gripper: low transmission, high stacking, breaking the traditional high-speed palletizing machine can't delivery in the form of low.

Adopt advanced manufacturing process, Adopt advanced manufacturing process: stacker crane column, beam slide rail and mounting holes are one-time installed and processed in high precision milling planer. High precision,low noise and more stable.

According to the instruction, the machine fully automatic operation, automatic fault detection and alarm, high safety and reliability. saving an area of 1/3 compared with the traditional stacker, energy consumption is 1/3 of the original.

Equipment can realize the cartons code stamping or shrink film packaging products. The machine is equipped with a variety of security measures.

技术参数

SPECIFICATION

设备型号Model	YCMD55	YCMD55D
生产能力Capacity	55箱/分钟(cases/min)	42-60箱/分钟(cases/min)
工作压力Work Air Pressure	0.6~0.8Mpa	
设备总功率Rated Power	19Kw	23Kw
设备重量Weight	9580Kg	11000Kg
机型尺寸Dimension of Machine	L14100mm*W7100mm*H4000mm	14100mm*7900mm*4000mm
堆码高度Max Loading Height	1700mm	
堆码重量Max Loading Weight	1600kg	