

散热器,暖气片

产品名称	散热器,暖气片
公司名称	北京恒邦凯捷散热器有限公司
价格	.00/个
规格参数	型号:MZ2-5/1800 材质:钢 规格:1800*295*78mm
公司地址	中国 北京市 北京市丰台区海鹰路8号金伟凯生物科技园1号楼3层
联系电话	86 010 63713861-600 13141465263

产品详情

型号	MZ 2-5/1800	材质	钢
规格	1800*295*78mm	管径	6分
表面处理 类型	喷塑 串片	安装型式	上进下出等多种

基本技术参数:

型号	mz 2-5/1800
材质	钢
尺寸(h*w*t mm)	1800*295*78
接口距	1755/59mm
散热量(watts)	1457.5
工作压力	1.2 mpa
测试压力	2.0mpa
排数	1

2003年,凯捷散热器顺利通过iso9001:2000国际质量体系人证.同时,为充分保障经销商、建材城以及广大消费者的利益,凯捷全部散热器产品由中国人民保险公司公司承保。凯捷散热器不仅是高品质产品的象征,更是维护行业良好信誉的先行者!

凯捷散热器的主要优点:

材料采用优质高价低碳钢钢管,壁厚1.5mm。

表面除油、除锈、表调、磷化,采用德国散热器标准din55900阴极电泳上底漆,烘干后再喷塑,面漆光亮且光滑,高温潮湿环境下不生锈、不变色,无异味。

表面喷涂采用高质高价纯聚脂粉末户外型，耐紫外线性强，不变色。

内壁采用武汉材料保护研究所的有机内防腐涂料处理。

凯捷散热器静压试验压力为2mpa,高于国家标准的1.5mpa的试验压力。

凯捷散热器造型秀气典雅,表面喷涂光滑细致,颜色绚丽,环保无污染.散热量高,质量好，使用寿命长，价格合理，性价比高，是您的不二选择！

effective radiating system.

rigorous interior corrosion-resistant process applied.

long workable life.

cathode electrophoresis of german radiator ' s specification din 55900 applied.

laser logo provided.

oem/odm are welcome!

packing: individually packed with blistered poly bag and 5-layer carton, then in pallets. inside you will find a box with the accessory kit.