

## (手套、皮包、玩具、) 液压摇摆下料机

|      |                                       |
|------|---------------------------------------|
| 产品名称 | (手套、皮包、玩具、) 液压摇摆下料机                   |
| 公司名称 | 盐城市盐都区远鸿机械厂                           |
| 价格   | .00/个                                 |
| 规格参数 | 类型:摇臂裁断机<br>品牌:远鸿<br>型号:xclp-2/20     |
| 公司地址 | 盐城市盐都区大冈镇新冈中路                         |
| 联系电话 | 86 0515 88088939/88852823 18962085939 |

## 产品详情

|        |                 |           |                           |
|--------|-----------------|-----------|---------------------------|
| 类型     | 摇臂裁断机           | 品牌        | 远鸿                        |
| 型号     | xclp-2/20       | 主电机功率     | 1.5 ( kw )                |
| 裁断力    | 20 ( T )        | 上速度       | 0.2 ( mm/s )              |
| 下速度    | 0.18 ( mm/s )   | 裁断面积      | 50*35 ( mm <sup>2</sup> ) |
| 工作台尺寸  | 1000*500 ( mm ) | 上压板至工作台距离 | 160 ( mm )                |
| 冲程调节范围 | 75              |           |                           |

用途与特点 本机适用于皮革、塑料、布类、皮包、玩具、帽子、发泡片、地板材料、软木片等各种需要用刀模裁断的裁剪物。1. 摆臂可以自动摆动，操作视线极佳，特别适用于对真皮的下料裁断。2. 采用双手操作开关，保证操作人员的安全性。3. 立柱配有自润滑系统，不需人工加油，提高了机器的使用寿命。4. 液压系统在封闭的环境下运转，在一般的工作环境下可以工作。5. 根据类型本机可分为标准型、微电脑型、加宽型、微电脑加宽型四种。

this machine is mainly suitable for cutting materials like leather, plastic, cloth leather bags, toys, hats, spongy floss pieces floor materials, soft wood pieces and materials needed cutting out. 1. the swing arm can swing automatically. best operation line of sight, especially suitable for laying-off and cutting of true skin. 2. the adoption of double-hand operation ensures safety for operators. 3. the pilar equipped with self-lubricating system doesneed any hand lubrication, the machine usage life hence is improved. 4. the hydraulic system operates under enclosed

environment, it requires little to the working environment. 5 . according to types, the machine can be classified into standard type, micro computer type, widening type and micro computer widening type etc. four types.

|  |  |                           |
|--|--|---------------------------|
| 最大冲裁力 maximum momentum                   |  | 200kn                     |
| 冲裁速度 seissor speed                       |  | 0.06m/s                   |
| 行程调节范围 stroke adjustment                 |  | 0—75mm                    |
| 上下压板间距离 range between the working tables |  | 65—150mm                  |
| 上摆臂尺寸 upper rocker dimensions            |  | 350 × 500mm   450 × 500mm |
| 下工作台面尺寸 size of the pressing board       |  | 1000 × 500mm              |
| 电机功率 motor power                         |  | 1.5kw                     |
| 外形尺寸 overall dimension                   |  | 1000 × 1050 × 1480mm      |
| 整机重量 total weight                        |  | 1050kg                    |