

# 矿用多级泵 0.88 ( Mpa )

产品名称	矿用多级泵 0.88 ( Mpa )
公司名称	洛阳乾晨机械设备有限公司
价格	.00/个
规格参数	是否提供加工定制:否 压力:0.88 ( Mpa ) 材质:铸铁
公司地址	中国 河南 洛阳市西工区 洛阳市西工区唐宫西路36号唐宫大厦512室
联系电话	086 0379 63203379 13937961082

## 产品详情

是否提供加工定制	否	压力	0.88 ( Mpa )
材质	铸铁	泵轴位置	卧式
叶轮吸入方式	单吸式	品牌	长沙
型号	D型泵	适用范围	排水
流量	10-500 ( m3/h )	扬程	30-1000 ( m )
叶轮结构	封闭式	叶轮数目	多级
产地	运城	工作压力	0.88Mpa

dg 12-25 × 7	2950	7.5	2.08	197.4	44	9.16	15
		12.5	3.47	175	54	11.0	
		15.0	4.17	161	53	12.41	
d dg 12-25 × 8	2950	7.5	2.08	225.6	44	10.47	18.5
		12.5	3.47	200	54	12.51	
		15.0	4.17	184	53	14.18	
d dg 12-25 × 9	2950	7.5	2.08	253.8	44	11.78	18.5
		12.5	3.47	225	54	14.18	
		15.0	4.17	207	53	15.95	
d dg 12-25 × 10	2950	7.5	2.08	282	44	13.09	22
		12.5	3.47	250	54	15.76	
		15.0	4.17	230	53	17.73	
d dg 12-25 × 11	2950	7.5	2.08	310.2	44	14.4	22
		12.5	3.47	275	54	17.34	
		15.0	4.17	253	53	19.5	
d dg 12-25 × 12	2950	7.5	2.08	338.4	44	15.7	30
		12.5	3.47	300	54	18.9	

		15.0	4.17	276	53	27.3	
d dg 25-30 × 3	2950	15	4.17	102	50	8.33	15
		25	6.94	90	62	9.88	
		30	8.33	82.6	63	10.7	
d dg 25-30 × 4	2950	15	4.17	136	50	11.11	18.5
		25	6.94	120	62	13.1	
		30	8.33	110	63	14.26	
d dg 25-30 × 5	2950	15	4.17	170	50	13.89	22
		25	6.94	150	62	16.47	
		30	8.33	137.5	63	17.83	
d dg 25-30 × 6	2950	15	4.17	204	50	16.67	30
		25	6.94	180	62	19.77	
		30	8.33	165	63	21.4	
d dg 25-30 × 7	2950	15	4.17	238	50	19.44	30
		25	6.94	210	62	23.1	
		30	8.33	192.5	63	24.90	
d dg 25-30 × 8	2950	15	4.17	272	50	22.22	37
		25	6.94	240	62	26.4	
		30	8.33	220	63	28.53	
d dg 25-30 × 9	2950	15	4.17	306	50	25.0	37
		25	6.94	270	62	29.65	
		30	8.33	247.5	63	32.1	
d dg 25-30 × 10	2950	15	4.17	340	50	27.8	45
		25	6.94	300	62	32.9	
		30	8.33	275	63	35.7	
d dg 46-30 × 3	2950	30	8.33	102	64	13.02	22
		46	12.5	90	70	16.11	
		55	15.3	81	68	17.84	
d dg 46-30 × 4	2950	30	8.33	136	64	17.36	30
		46	12.8	120	70	21.48	
		55	15.3	108	68	23.79	
d dg 46-30 × 5	2950	30	8.33	170	64	21.7	37
		46	12.8	150	70	26.85	
		55	15.3	135	68	29.74	
d dg 46-30 × 6	2950	30	8.33	204	64	26.04	37
		46	12.8	180	70	32.21	
		55	15.3	162	68	35.68	
d dg 46-30 × 7	2950	30	8.33	238	64	30.38	45
		46	12.8	210	70	37.58	
		55	15.3	189	68	41.63	
d dg 46-30 × 8	2950	30	8.33	274	64	34.72	55
		46	12.8	240	70	42.95	
		55	15.3	216	68	47.58	
d dg 46-30 × 9	2950	30	8.33	306	64	39.06	55
		46	12.8	270	70	48.32	
		55	15.3	243	68	53.53	
d dg 46-30 × 10	2950	30	8.33	340	64	43.4	75
		46	12.8	300	70	53.69	
		55	15.3	270	344	59.47	
d dg 46-50 × 3	2950	30	8.33	166.5	54	25.19	37
		46	12.8	150	63	29.83	

		55	15.3	138	64	32.3	
d dg 46-50 × 4	2950	30	8.33	222	54	33.59	45
		46	12.8	200	63	39.77	
		55	15.3	184	64	43.06	
d dg 46-50 × 5	2950	30	8.33	277.5	54	41.98	55
		46	12.8	250	63	49.71	
		55	15.3	230	64	53.83	
d dg 46-50 × 6	2950	30	8.33	333	54	50.38	75
		46	12.8	300	63	59.65	
		55	15.3	276	64	64.59	
d dg 46-50 × 7	2950	30	8.33	388.5	54	58.78	75
		46	12.8	250	63	69.6	
		55	15.3	322	64	72.36	90
d dg 46-50 × 8	2950	30	8.33	440	54	67.18	90
		46	12.8	400	63	79.54	
		55	15.3	368	64	86.12	
d dg 46-50 × 9	2950	30	8.33	499.5	54	75.57	110
		46	12.8	450	63	89.48	
		55	15.3	414	64	96.89	