

# 欧洲密封P9020,碳纤维添加特种润滑油脂盘根

产品名称	欧洲密封P9020,碳纤维添加特种润滑油脂盘根
公司名称	福州众宝机电设备有限公司
价格	.00/个
规格参数	样品或现货:现货 是否标准件:标准件 品牌:欧洲密封
公司地址	福州市鼓楼区东街街道东街59号三山大厦（现龙盛大厦）北楼11层03室
联系电话	0591-87609488 13599417411

## 产品详情

样品或现货	现货	是否标准件	标准件
品牌	欧洲密封	型号	ES-P9020
盘根材质	碳纤维	使用温度	-200 ~ +250 ( )

构成： 碳纤维添加特种润滑油脂盘根

特性： a.在腐蚀性介质中总是能绝对地保护轴杆；b.优良的热平衡结构，体积稳定，非常小的热收缩，极好的；c.优良的化学和物理性能；d.适用于防挤出环。

适用： 锅炉给水泵、离心泵、搅拌机、搅拌器、揉和装置、匀料机等。

行业： 适用于发电厂、锅炉、造纸和制浆、化工和制药。

carbon fibre with special impregnated silicon free running in (non-asbestos)

main areas of application:

boiler-water feed pumps , centrifugal pumps , blenders , agitators , car boards , kneading devices , refiners , a

characteristics:

--highest practical standardization possibilities--protected against wear and tear with respect to abrasive fluids , nevertheless , extremely protective towards the shaft--thermally well-proportioned structure , volume stable little shrinking , excellent heat conductivity--excellent chemical and physical properties--suitable as a chamber ring for power stations , boiler houses , paper and pulp , chemicals and pharmaceuticals

	阀门	往复泵	旋转泵
压强p(bar)	100	60	20
速度v(m/s)		10	15
温度t( )	-200 ~ +250		
ph值	0 ~ 14		